

## 4-channel transmitter Liquiline CM444R

Expandable multiparameter DIN-rail and cabinet device for all industries



F L E X

### Benefits:

- **Saves space, saves money:**  
Small footprint, 4 channels in one device, expandable at any time, saves space in cabinets – perfect for skids.
- **High-speed installation:**  
No cut-out in cabinet door, one-click DIN-rail mounting, minimized wiring.
- **Simple and safe commissioning:**  
Saving configuration on SD card enables fast set-up on duplicate installations.
- **Easy to operate and service:**  
Intuitive user interface, hot plug & play with pre-calibrated Memosens sensors, universal components fit all parameters.
- **Process control from a distance:**  
Integrated web server that allows the operator to remotely view diagnostic data, perform configurations, or access device parameters in any web browser - even via Smartphone.
- **Higher availability, lower costs:**  
Heartbeat Technology enables status-oriented maintenance and easy verification of the entire measuring point and helps to carry out optimization measures.
- **Drive connectivity:** **Liquiline Edge Module CYY7** transfers process data to Netilion, independently of the fieldbus. This allows remote overview and the use of IIoT services. It's available in new products or as upgrade to installed Liquiline platforms.

More information and current pricing:

[www.endress.com/CM444R](http://www.endress.com/CM444R)

### Specs at a glance

▪

**Input** 1 to 4x Memosens digital input 2x 0/4 to 20mA Input optional 2 to 4x Digital input optional

- **Output / communication** 2 to 8x 0/4 to 20 mA current outputs, alarmrelay, 4x relay, ProfibusDP, Modbus RS485, Modbus TCP, Ethernet
- **Ingress protection** Transmitter: IP20 Optional Display: IP66

**Field of application:** Liquiline CM444R allows you to connect up to 4 Memosens sensors of your choice from over 12 measurement parameters. With its compact design, it fits into any cabinet and can be expanded at any time with inputs, outputs, controllers, math modules, and sensor channels. The transmitter belongs to the Liquiline platform with standardized system integration, operation, and spare parts. Heartbeat Technology helps you find the ideal balance between measurement point availability and maintenance costs.

## Features and specifications

pH

### Measuring principle

Potentiometric

### Application

Modular 4 wire controller

Multichannel: 1 to 4 digital channels for Memosens protocol

Multiparameter: pH, redox, ISFET, conductivity inductive and conductive, dissolved oxygen, nitrate and turbidity

4 sensors connectable in any combination

Functionality modular extendable at any time

Plug and play for modules and sensors

### Characteristic

Robust plastic housing

All non-ex applications

## pH

**Design**

2 to 4x Memosens input, 2 to 8x current output,  
Alarmrelay, 4x relay, SD card for software update and copy & paste of  
setup

**Material**

DIN rail housing: PC-FR  
Display seal: EPDM

**Dimension**

220 x 100 x 97 mm  
8.66 x 3.94 x 3.82 inch

**Process temperature**

0 to 55 °C (32 to 130 °F)

**Ingress protection**

Transmitter: IP20  
Optional Display: IP66

**Input**

1 to 4x Memosens digital input  
2x 0/4 to 20mA Input optional  
2 to 4x Digital input optional

**Output / communication**

2 to 8x 0/4 to 20 mA current outputs, alarmrelay,  
4x relay, ProfibusDP, Modbus RS485, Modbus TCP, Ethernet

**Additional certifications**

EAC, cCSAus

## ORP / Redox

**Measuring principle**

Sensor ORP / Redox

## ORP / Redox

### Application

Modular 4 wire controller

Multichannel: 1 to 4 digital channels for Memosens protocol

Multiparameter: pH, redox, ISFET, conductivity inductive and conductive, dissolved oxygen, nitrate and turbidity

4 sensors connectable in any combination

Functionality modular extendable at any time

Plug and play for modules and sensors

### Characteristic

Robust plastic housing

All non-ex applications

### Design

2 to 4x Memosens input, 2 to 8x current output

Alarmrelay, 4x relay, SD card for software update and copy & paste of setup

### Material

DIN rail housing: PC-FR

Display seal: EPDM

### Dimension

220 x 100 x 97 mm

8.66 x 3.94 x 3.82 inch

### Process temperature

0 to 55 °C (32 to 130 °F)

### Ingress protection

Transmitter: IP20

Optional Display: IP66

### Input

1 to 4x Memosens digital input

2x 0/4 to 20mA Input optional

2 to 4x Digital input optional

---

**ORP / Redox****Output / communication**

2 to 8x 0/4 to 20 mA current outputs, alarmrelay,  
4x relay, ProfibusDP, Modbus RS485, Modbus TCP, Ethernet

---

**Additional certifications**

EAC, cCSAus

---

**Conductivity****Measuring principle**

Conductive

---

**Application**

Modular 4 wire controller

Multichannel: 1 to 4 digital channels for Memosens protocol

Multiparameter: pH, redox, ISFET, conductivity inductive and conductive,  
dissolved oxygen, nitrate and turbidity

4 sensors connectable in any combination

Functionality modular extendable at any time

Plug and play for modules and sensors

---

**Characteristic**

Robust plastic housing

All non-ex applications

---

**Design**

2 to 4x Memosens input, 2 to 8x current output

Alarmrelay, 4x relay, SD card for software update and copy & paste of  
setup

---

**Material**

DIN rail housing: PC-FR

Display seal: EPDM

---

**Dimension**

220 x 100 x 97 mm

8.66 x 3.94 x 3.82 inch

---

## Conductivity

### Process temperature

0 to 55 °C (32 to 130 °F)

### Ingress protection

Transmitter: IP20

Optional Display: IP66

### Input

1 to 4x Memosens digital input

2x 0/4 to 20mA Input optional

2 to 4x Digital input optional

### Output / communication

2 to 8x 0/4 to 20 mA current outputs, alarmrelay,

4x relay, ProfibusDP, Modbus RS485, Modbus TCP, Ethernet

### Additional certifications

EAC, cCSAus

## Oxygen

### Measuring principle

Amperometric oxygen measurement

### Application

Modular 4 wire controller

Multichannel: 1 to 4 digital channels for Memosens protocol

Multiparameter: pH, redox, ISFET, conductivity inductive and conductive, dissolved oxygen, nitrate and turbidity

4 sensors connectable in any combination

Functionality modular extendable at any time

Plug and play for modules and sensors

### Characteristic

Robust plastic housing

All non-ex applications

## Oxygen

### Design

2 to 4x Memosens input, 2 to 8x current output,  
Alarmrelay, 4x relay, SD card for software update and copy & paste of  
setup

### Material

DIN rail housing: PC-FR  
Display seal: EPDM

### Dimension

220 x 100 x 97 mm  
8.66 x 3.94 x 3.82 inch

### Process temperature

0 to 55 °C (32 to 130 °F)

### Input

1 to 4x Memosens digital input  
2x 0/4 to 20mA Input optional  
2 to 4x Digital input optional

### Output / communication

2 to 8x 0/4 to 20 mA current outputs, alarmrelay,  
4x relay, ProfibusDP, Modbus RS485, Modbus TCP, Ethernet

### Additional certifications

EAC, cCSAus

## Disinfection

### Measuring principle

Total chlorine

## Disinfection

### Application

Modular 4 wire controller

Multichannel: 1 to 4 digital channels for Memosens protocol

Multiparameter: pH, redox, ISFET, conductivity inductive and conductive, dissolved oxygen, nitrate and turbidity

4 sensors connectable in any combination

Functionality modular extendable at any time

Plug and play for modules and sensors

### Characteristic

Robust plastic housing

All non-ex applications

### Design

2 to 4x Memosens input, 2 to 8x current output,

Alarmrelay, 4x relay, SD card for software update and copy & paste of setup

### Material

DIN rail housing: PC-FR

Display seal: EPDM

### Dimension

220 x 100 x 97 mm

8.66 x 3.94 x 3.82 inch

### Process temperature

0 to 55 °C (32 to 130 °F)

### Input

1 to 4x Memosens digital input

2x 0/4 to 20mA Input optional

2 to 4x Digital input optional

### Output / communication

2 to 8x 0/4 to 20 mA current outputs, alarmrelay,

4x relay, ProfibusDP, Modbus RS485, Modbus TCP, Ethernet



---

## Disinfection

### Additional certifications

EAC, cCSAus

---

## Turbidity

### Measuring principle

Single beam scattered light

---

### Application

Modular 4 wire controller

Multichannel: 1 to 4 digital channels for Memosens protocol

Multiparameter: pH, redox, ISFET, conductivity inductive and conductive, dissolved oxygen, nitrate and turbidity

4 sensors connectable in any combination

Functionality modular extendable at any time

Plug and play for modules and sensors

---

### Characteristic

Robust plastic housing

All non-ex applications

---

### Design

2 to 4x Memosens input, 2 to 8x current output,

Alarmrelay, 4x relay, SD card for software update and copy & paste of setup

---

### Material

DIN rail housing: PC-FR

Display seal: EPDM

---

### Dimension

220 x 100 x 97 mm

8.66 x 3.94 x 3.82 inch

---

### Process temperature

0 to 55 °C (32 to 130 °F)

---

## Turbidity

### Ingress protection

Transmitter: IP20

Optional Display: IP66

### Input

1 to 4x Memosens digital input

2x 0/4 to 20mA Input optional

2 to 4x Digital input optional

### Output / communication

2 to 8x 0/4 to 20 mA current outputs, alarmrelay,

4x relay, ProfibusDP, Modbus RS485, Modbus TCP, Ethernet

### Additional certifications

EAC, cCSAus

## Sludge Level

### Measuring principle

Ultrasonic sensor

### Application

Modular 4 wire controller

Multichannel: 1 to 4 digital channels for Memosens protocol

Multiparameter: pH, redox, ISFET, conductivity inductive and conductive, dissolved oxygen, nitrate and turbidity

4 sensors connectable in any combination

Functionality modular extendable at any time

Plug and play for modules and sensors

### Characteristic

Robust plastic housing

All non-ex applications

### Design

2 to 4x Memosens input, 2 to 8x current output,

Alarmrelay, 4x relay, SD card for software update and copy & paste of setup

## Sludge Level

**Material**

DIN rail housing: PC-FR

Display seal: EPDM

**Dimension**

220 x 100 x 97 mm

8.66 x 3.94 x 3.82 inch

**Process temperature**

0 to 55 °C (32 to 130 °F)

**Ingress protection**

Transmitter: IP20

Optional Display: IP66

**Input**

1 to 4x Memosens digital input

2x 0/4 to 20mA Input optional

2 to 4x Digital input optional

**Output / communication**

2 to 8x 0/4 to 20 mA current outputs, alarmrelay,

4x relay, ProfibusDP, Modbus RS485, Modbus TCP, Ethernet

**Additional certifications**

EAC, cCSAus

More information [www.endress.com/CM444R](http://www.endress.com/CM444R)